



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C10M 169/04		A1	(11) International Publication Number: WO 97/16511
			(43) International Publication Date: 9 May 1997 (09.05.97)
(21) International Application Number: PCT/US96/17414		(81) Designated States: AU, CA, JP, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 1 November 1996 (01.11.96)			
(30) Priority Data: 552,967 3 November 1995 (03.11.95) US		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(71) Applicant: EXXON CHEMICAL PATENTS INC. [US/US]; 1900 East Linden Avenue, P.O. Box 710, Linden, NJ 07036 (US).			
(72) Inventors: WATTS, Raymond, Frederick; 7 Oxford Lane, Long Valley, NJ 07853 (US). TANDON, Manoj; 30 Lehigh Court, Princeton, NJ 08540 (US).			
(74) Agent: SHATYNSKI, Theodore, J.; Exxon Chemical Company, 1900 East Linden Avenue, P.O. Box 710, Linden, NJ 07036 (US).			

(54) Title: AUTOMATIC TRANSMISSION FLUIDS WITH IMPROVED TRANSMISSION PERFORMANCE

4L60 CYCLING TEST DATA

ACID NUMBER INCREASE vs. CYCLES



(57) Abstract

Power transmitting fluids, especially automatic transmission fluids, possess improved properties such as antiwear, durability, antioxidation, and shift-time performance by incorporation of high viscosity polyalphaolefins.

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

- 1 -

AUTOMATIC TRANSMISSION FLUIDS
WITH IMPROVED TRANSMISSION PERFORMANCE

5

BACKGROUND OF THE INVENTION

This invention relates to power transmitting fluids, particularly automatic transmission fluids, of enhanced performance capabilities.

10 Automobile builders continually strive to produce more durable vehicles. Overall vehicle durability is a function of the durability of each of the components in the vehicle, e.g., the engine, transmission, etc. In order to improve overall vehicle durability, the durability of every major component in the vehicle must be improved. To improve the durability of the automatic
15 transmission, automatic transmission fluids (ATF's) of improved performance must be produced. Relative performance of an automatic transmission fluid can be determined by evaluating the consistency of transmission shifts with increasing time or mileage, the extent to which the transmission has worn, and the extent to which the ATF has oxidized and sheared (lost viscosity).
20 What we have now found is a method of simultaneously improving all of these ATF performance characteristics.

 Although many 'bench' tests have been devised to evaluate ATF performance, e.g., SAE #2 friction test machines and Vickers vane pump
25 tests, the best assessment of transmission durability is gained from running an actual transmission. Running a transmission in an extremely severe operating regime, under highly controlled conditions, is quite difficult. However, General Motors has devised such a test. It is described in the General Motors DEXRON®-III specification as the 4L60 Cycling Test (ATF
30 Specification GM-6297M, April 1993, Appendix F). In this test a full automobile driveline (engine and transmission) is loaded by means of an energy absorption dynamometer. The dynamometer is programmed to simulate the inertia of a fully laden vehicle. With the transmission sump temperature held at 135°C, the engine is accelerated from idle to 3400 rpm
35 under full throttle conditions. Each acceleration from idle to 3400 rpm is termed a 'cycle'. A standard test consists of 20,000 cycles. This test correlates very well with severe field service. Using this test to evaluate overall transmission durability and fluid degradation, what we have now

- 2 -

found, is that ATF's that contain a minor amount of a high viscosity polyalphaolefin as part of the base oil mixture provide unexpected good transmission durability.

5

SUMMARY OF THE INVENTION

This invention describes a power transmission fluid, adaptable as an automatic transmission fluid, that provides significantly improved power
10 transmission device durability and service life. This invention is comprised of:

(1) a major amount of a lubricating oil comprising:

(a) no less than 50 weight percent of a natural lubricating oil having a kinematic viscosity from 1 to 10 mm²/s when measured at 100°C,

15 (b) from 0 to 49 weight percent of a synthetic lubricating oil having a viscosity from 1 to 10 mm²/s when measured at 100°C,

(c) from 1 to 25 weight percent of a high viscosity polyalphaolefin having a kinematic viscosity from 40 to 500 mm²/s when measured at 100°C; and

20

(2) a minor amount of an automatic transmission fluid additive package.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 depicts fluid acid number increase as a function of test cycles according to the General Motors DEXRON®-III, 4L60 Cycling Test.

30

Figure 2 depicts fluid copper content as a function of test cycles according to the General Motors DEXRON®-III, 4L60 Cycling Test.

Figure 3 depicts fluid 1-2 shift time as a function of test cycles according to the General Motors DEXRON®-III, 4L60 Cycling Test.

35

Figure 4 depicts fluid kinematic viscosity as a function of test cycles according to the General Motors DEXRON®-III, 4L60 Cycling Test.

DETAILED DESCRIPTION OF THE INVENTION

5 What has now been found is that incorporation of minor amounts of high viscosity polyalphaolefins in automatic transmission fluids, produces automatic transmission fluids of exceptional service life. These transmission fluids also provide unexpectedly good wear protection and shift durability to the transmissions they are used in.

10

 While the invention is demonstrated for a particular power transmitting fluid, i.e., an ATF, it is contemplated that the benefits of this invention are equally applicable to other power transmitting fluids. Examples of other types of power transmitting fluids included within the scope of this invention are
15 manual transmission oils, gear oils, hydraulic fluids, heavy duty hydraulic fluids, industrial oils, power steering fluids, pump oils, tractor fluids, universal tractor fluids, and the like. These power transmitting fluids can be formulated with a variety of performance additives and a variety of base oils.

20 Lubricating Oils

 Lubricating oils useful in this invention are derived from natural lubricating oils, synthetic lubricating oils, and their mixtures. In general, both the natural and synthetic lubricating oil will each have a kinematic viscosity
25 ranging from about 1 to about 10 mm²/s (cSt) at 100°C.

Natural Lubricating Oils

 Natural lubricating oils include animal oils, vegetable oils (e.g., castor
30 oil and lard oil), petroleum oils, mineral oils, and oils derived from coal or shale.

 The natural lubricating oils will be present in this invention in amounts no less than 50, preferably from 50 to 90, most preferably from 60 to 85
35 weight percent in the finished fluid.

The preferred natural lubricating oil is mineral oil. Suitable mineral oils include all common mineral oil basestocks. This includes oils that are naphthenic or paraffinic in chemical structure. Oils that are refined by conventional methodology using acid, alkali, and clay or other agents such as aluminum chloride, or they may be extracted oils produced, for example, by solvent extraction with solvents such as phenol, sulfur dioxide, furfural, dichloroethyl ether, etc. They may be hydrotreated or hydrofined, dewaxed by chilling or catalytic dewaxing processes, or hydrocracked. The mineral oil may be produced from natural crude sources or be composed of isomerized wax materials or residues of other refining processes.

The mineral oils may be derived from refined, rerefined oils, or mixtures thereof. Unrefined oils are obtained directly from a natural source or synthetic source (e.g., coal, shale, or tar sands bitumen) without further purification or treatment. Examples of unrefined oils include a shale oil obtained directly from a retorting operation, a petroleum oil obtained directly from distillation, or an ester oil obtained directly from an esterification process, each of which is then used without further treatment. Refined oils are similar to the unrefined oils except that refined oils have been treated in one or more purification steps to improve one or more properties. Suitable purification techniques include distillation, hydrotreating, dewaxing, solvent extraction, acid or base extraction, filtration, and percolation, all of which are known to those skilled in the art. Rerefined oils are obtained by treating used oils in processes similar to those used to obtain the refined oils. These rerefined oils are also known as reclaimed or reprocessed oils and are often additionally processed by techniques for removal of spent additives and oil breakdown products.

Typically the mineral oils will have kinematic viscosities of from 2.0 to 8.0 mm²/s (cSt) at 100°C. The preferred mineral oils have kinematic viscosities of from 2 to 6 mm²/s (cSt), and most preferred are those mineral oils with viscosities of 3 to 5 mm²/s (cSt) at 100°C.

Synthetic Lubricating Oils

The synthetic lubricating oils of the present invention will comprise from 0 to 49, preferably from 0 to 40, most preferably from 0 to 25 weight percent of the finished fluid.

Synthetic lubricating oils include hydrocarbon oils and halo-substituted hydrocarbon oils such as oligomerized, polymerized, and interpolymerized olefins [e.g., polybutylenes, polypropylenes, propylene, isobutylene copolymers, chlorinated polylactenes, poly(1-hexenes), poly(1-octenes), poly(1-decenes) etc., and mixtures thereof]; alkylbenzenes [e.g., dodecylbenzenes, tetradecylbenzenes, dinonyl-benzenes, di(2-ethylhexyl)benzene, etc.]; polyphenyls [e.g., biphenyls, terphenyls, alkylated polyphenyls, etc.]; and alkylated diphenyl ethers, alkylated diphenyl sulfides, as well as their derivatives, analogs, and homologs thereof, and the like. Preferred oils from this group of synthetic oils are oligomers of polyalphaolefins, particularly oligomers of 1-octene and 1-decene.

Synthetic lubricating oils also include alkylene oxide polymers, interpolymers, copolymers, and derivatives thereof where the terminal hydroxyl groups have been modified by esterification, etherification, etc. This class of synthetic oils is exemplified by: polyoxyalkylene polymers prepared by polymerization of ethylene oxide or propylene oxide; the alkyl and aryl ethers of these polyoxyalkylene polymers (e.g., methyl-polyisopropylene glycol ether having an average molecular weight of 1000, diphenyl ether of polypropylene glycol having a molecular weight of 1000 - 1500); and mono- and poly-carboxylic esters thereof (e.g., the acetic acid esters, mixed C₃-C₈ fatty acid esters, and C₁₂ oxo acid diester of tetraethylene glycol).

Another suitable class of synthetic lubricating oils comprises diesters which are the esters of dicarboxylic acids (e.g., phthalic acid, succinic acid, alkyl succinic acids and alkenyl succinic acids, maleic acid, azelaic acid, suberic acid, sebacic acid, fumaric acid, adipic acid, linoleic acid dimer, malonic acid, alkylmalonic acids, alkenyl malonic acids, etc.) with a variety of alcohols (e.g., butyl alcohol, hexyl alcohol, dodecyl alcohol, 2-ethylhexyl alcohol, ethylene glycol, diethylene glycol monoethers, propylene glycol, etc.). Specific examples of these esters include dibutyl adipate, di(2-ethylhexyl)

- 6 -

sebacate, di-n-hexyl fumarate, dioctyl sebacate, diisooctyl azelate, diisodecyl azelate, dioctyl phthalate, didecyl phthalate, dieicosyl sebacate, the 2-ethylhexyl diester of linoleic acid dimer, and the complex ester formed by reacting one mole of sebacic acid with two moles of tetraethylene glycol and two moles of 2-ethyl-hexanoic acid, and the like. A preferred type of oil from this class of synthetic oils are adipates of C₄ to C₁₂ alcohols.

Esters useful as synthetic lubricating oils also include those made from C₅ to C₁₂ monocarboxylic acids with polyols and/or polyol ethers. Examples of polyols are neopentyl glycol, trimethylolpropane pentaerythritol, and the like. Common polyol ethers are dipentaerythritol, tripentaerythritol, and the like. Specific examples of polyol esters derived from either linear or branched chain acids, or mixtures thereof, would include: trimethylolpropane trisebacate; pentaerythritol tetrapentanoate; trimethylolpropane trioctanoate; neopentylglycol didecanoate; pentaerythritol tetraoctanoate, and dipenterythritol hexapentanoate.

The preferred synthetic oils are polyalphaolefins, diesters, and polyol esters as previously described having kinematic viscosities from 2 to 8, most preferably from 3 to 5 mm²/s when measured at 100°C.

High Viscosity Polyalphaolefins

Polyalphaolefins (PAO's) are oligomers of terminally unsaturated alkenes. The polyalphaolefins of the current invention are characterized by their viscosities. For purposes of this invention, the high viscosity polyalphaolefins are defined as possessing kinematic viscosities at 100°C of from about 40 to about 500 mm²/s (cSt). Production of high viscosity polyalphaolefins is well known in the art and is described for example in U.S. 4,041,098.

The preferred polyalphaolefins are made from 1-octene, 1-decene, or mixtures thereof. They can be saturated or unsaturated. The preferred PAO's have kinematic viscosities at 100°C from about 40 to about 150, most preferably 100 mm²/s (cSt). These materials can be obtained commercially for instance as SYNTON® PAO-40 and SYNTON® PAO-100 from Uniroyal Chemical Co.

- 7 -

The compositions of this invention will contain a minor amount of the high viscosity polyalphaolefin. Typically, amounts range from 1 to 25, preferably from 2 to 20, most preferably 5 to 15 weight percent in the finished fluid.

Automatic Transmission Fluid Additive Packages

Automatic transmission fluid additive packages are well known in the art. They confer to a base oil composition the required characteristics to make that base oil function acceptably in an automatic transmission. These characteristics would include, but not be limited to, oxidation stability, wear protection, friction control, dispersancy, low temperature fluidity, seal swell, and foam suppression. A typical automatic transmission fluid additive package would have a composition such as shown below:

	<u>COMPONENT</u>	<u>MASS %</u>
	Ashless Dispersant	56.250
20	Anti-wear Agent	6.250
	Anti-oxidant	6.250
	Corrosion Inhibitor	0.625
	Friction Modifier	3.125
	Seal Swell Agent	6.250
25	Pour Depressant	3.125
	Anti-foamant	0.625
	Diluent Oil	17.500

The additive package above is referred to a detergent inhibitor (DI) package. DI packages typically treat from 3 to 10 mass percent in the ATF.

The ATF additive package may also contain a viscosity modifier. In that case the additive is referred to as a combined package or DI/VI. An example of a DI/VI package is shown below:

	<u>COMPONENT</u>	<u>MASS %</u>
	DI Package (as above)	67.000
40	Viscosity Modifier	33.000

- 8 -

A DI/VI package typically treats at from 5 to 20 mass percent in the ATF.

Examples of commercially available ATF performance additive packages are: PARANOX[®] 440, PARANOX[®] 442, PARANOX[®] 445, and PARATORQ[®] 4520 sold by Exxon Chemical Company; Hitec[®] E-400, Hitec[®] E-403, Hitec[®] E-410, and Hitec[®] E-420 sold by Ethyl Additive Company; and Lubrizol[®] 6268, Lubrizol[®] 7900, and Lubrizol[®] 9600 sold by the Lubrizol Corporation.

EXAMPLES

The following examples are given as specific illustrations of the claimed invention. It should be understood, however, that the invention is not limited to the specific details set forth in the examples. All parts and percentages are by weight unless otherwise specified.

Four automatic transmission fluids, Fluids A, B, C, and D, were prepared for evaluation and their compositions are shown in Table 1. The base additive package used in these fluids contained conventional amounts of succinimide dispersant, antioxidants, an antiwear agent, a corrosion inhibitor, antifoamant, friction modifiers, and a diluent oil.

Table 1

TEST FLUIDS				
FLUIDS:	A	B	C	D
BASE ADDITIVE PACKAGE	8.00	8.00	8.00	8.00
ADDITIONAL CORROSION INHIBITOR	0.00	0.20	0.05	0.00
Petro-Canada 80HT BASE OIL (KV = 3.5 mm ² /s @ 100°C)	92.00	81.80	81.95	82.00
POLYMETHACRYLATE VI	0.00	0.00	4.00	0.00
PAO-4 (KV = 4 mm ² /s @ 100°C)	0.00	10.00	0.00	0.00
PAO-100 (KV = 100 mm ² /s @ 100°C)	0.00	0.00	0.00	10.00
KINEMATIC VISCOSITY @ 100°C	4.1	4.1	5.7	5.8

Fluids A-D were evaluated using a slight modification to the previously described GM DEXRON[®]-III 4L60 Cycling Test. The modification to the test was that instead of stopping the test at 20,000 cycles, the test was allowed to

continue for 30,000 cycles or until the transmission failed to operate, whichever occurred first. Only two of the fluids completed the 30,000 cycle test, Fluids A and D. Neither Fluid B nor Fluid C completed the 30,000 cycles. Fluid B was stopped at 26,632 cycles due to elongated 1 - 2 shift
5 times, and Fluid C was stopped at 27,564 cycles due to pump failure.

Figures 1 through 4 show the performance of the four fluids in the transmission cycling test. Figure 1 shows the increase in acid number of the fluid as a function of cycles. Fluids A and C have acid number increases in
10 the range of 1.5 units. Fluid B with the extra inhibitor and PAO-4, has a slightly lower acid number increase, approximately 1 unit. However, Fluid D, the fluid with 10% PAO-100, has by far the lowest acid number increase, i.e., less than 0.5 units.

15 Figure 2 shows the increase in copper content in the fluids versus test cycles. Fluid D has the lowest increase in copper during the test. Fluids B and C contain extra added corrosion inhibitors and still end up with more copper than Fluid D. Copper level can be equated with overall wear protection in the transmission.

20 Figure 3 shows 1-2 shift time as a function of cycles. The lines in Figure 3 are shown as trend lines since the data has some variability. Fluids B and C actually fail the test due to elongating shift times so their trend lines rise with increasing cycles. Fluids A and D complete the test so their trend
25 lines are of lower slope. Closer examination of the data indicates that the 1-2 shift times for Fluid D are the lowest and most consistent and thus represents the most desirable performance. The 1-2 shift times for Fluid A are quite variable.

30 Figure 4 shows viscosity as a function of test cycles. Fluid D containing the PAO-100 is the best performing fluid in all parameters, and it does have the highest viscosity. However, Fluid C, having the same fresh oil viscosity as Fluid D does not perform as well. Therefore, viscosity cannot be the sole reason Fluid D performs so well. Also, Fluid C loses over 10% of its
35 viscosity during the test, while the viscosity of Fluid D remains relatively unchanged.

- 10 -

All of this data taken together shows that Fluid D is by far the best performing fluid in this very severe test. It out performs straight mineral oil, a viscosity modified mineral oil with added corrosion inhibitor, and a mineral oil with 10% PAO-4 plus added corrosion inhibitors.

5

The principles, preferred embodiments, and modes of operation of the present invention have been described in the foregoing specification. The invention which is intended to be protected herein, however, is not to be construed as limited to the particular forms disclosed, since these are to be regarded as illustrative rather than instructive. Variations and changes may be made by those skilled in the art without departing from the spirit of the invention.

10

CLAIMS:

1. A power transmitting fluid, adaptable as an automatic transmission fluid, comprising:

(1) a major amount of a lubricating oil comprising:

(a) no less than 50 weight percent of a natural lubricating oil having a kinematic viscosity from 1 to 10 mm²/s when measured at 100°C,

(b) from 0 to 49 weight percent of a synthetic lubricating oil having a viscosity from 1 to 10 mm²/s when measured at 100°C,

(c) from 1 to 25 weight percent of a high viscosity polyalphaolefin having a kinematic viscosity from 40 to 500 mm²/s when measured at 100°C; and

(2) a minor amount of an automatic transmission fluid additive package.

2. The composition of claim 1, where the natural lubricating oil is a mineral oil and the synthetic oil is a polyalphaolefin, diester, polyol ester, or their mixtures.

3. The composition of claim 2, where the synthetic oil is a polyalphaolefin.

4. The composition of claim 3, where the mineral oil and polyalphaolefin have kinematic viscosities from 3 to 5 mm²/s measured at a temperature of 100°C.

5. The composition of claim 4, where the high viscosity polyalphaolefin has a kinematic viscosity from 40 to 150 mm²/s measured at 100°C.

6. The composition of claim 5, where the high viscosity polyalphaolefin has a kinematic viscosity of 100 mm²/s measured at 100°C.

- 12 -

7. The composition of claim 6, where the additive package contains at least one additive selected from the group consisting of ashless dispersants, antiwear agents, antioxidants, corrosion inhibitors, friction modifiers, seal swell agents, pour point depressants, antifoamants, and viscosity modifiers.
8. The composition of claim 7, where the power transmitting fluid is an automatic transmission fluid.
9. A method for improving the durability and service life of power transmission devices by using in the device the composition of claim 1.

Figure 1

4L60 CYCLING TEST DATA

ACID NUMBER INCREASE vs. CYCLES




Figure 2

4L60 CYCLING TEST DATA

COPPER CONTENT vs. CYCLES




Figure 3

4L60 CYCLING TEST DATA

1 - 2 SHIFT TIME vs. CYCLES





Figure 4

4L60 CYCLING TEST DATA

KINEMATIC VISCOSITY vs. CYCLES



INTERNATIONAL SEARCH REPORT

International Application No
PC1/US 96/17414

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C10M169/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 C10M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	W0 89 12665 A (MOBIL OIL) 28 December 1989 see the whole document ---	1-3,9
X	EP 0 604 408 A (LUBRIZOL) 29 June 1994 see page 8, line 35 - page 9, line 21; examples 1-3,5,6 ---	1-3,9
X	DE 19 06 674 A (I.F.P.) 9 October 1969 see claims 1,3,14; table 2 ---	1,9
X	US 3 637 503 A (GIANNETTI ET AL.) 25 January 1972 see the whole document ---	1
A	EP 0 088 453 A (UNIROYAL) 14 September 1983 see page 12, line 4 - line 7 ---	1-9
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

12 February 1997

Date of mailing of the international search report

27.02.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

De La Morinerie, B

INTERNATIONAL SEARCH REPORT

International Application No.

PC: /US 96/17414

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 361 180 A (IDEMITSU KOSAN) 4 April 1990 see table 2 ---	1-9
A	DE 25 24 118 A (NIPPON OIL) 4 December 1975 see claim 1 ---	1-9
A	GB 1 124 016 A (THE BRITISH PETROLEUM) 14 August 1968 see the whole document ---	1-9
A	GB 1 057 368 A (THE BRITISH PETROLEUM) 1 February 1967 see the whole document ---	1-9
A	EP 0 240 813 A (IDEMITSU KOSAN) 14 October 1987 see the whole document -----	1-9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 96/17414

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-8912665	28-12-89	US-A- 4912272	27-03-90
		AU-B- 633009	21-01-93
		AU-A- 3849689	12-01-90
		CA-A- 1331600	23-08-94
		DE-D- 68910136	25-11-93
		DE-T- 68910136	10-02-94
		EP-A- 0451142	16-10-91
		FI-B- 95925	29-12-95
		JP-T- 4502775	21-05-92
EP-A-604408	29-06-94	US-A- 4968853	06-11-90
		AT-T- 114161	15-12-94
		AU-A- 3214389	01-08-89
		CA-A- 1312696	12-01-93
		DE-D- 3852132	22-12-94
		DE-T- 3852132	01-06-95
		EP-A- 0349639	10-01-90
		WO-A- 8906247	13-07-89
		US-A- 5345024	06-09-94
		US-A- 5364994	15-11-94
DE-A-1906674	09-10-69	BE-A- 729786	18-08-69
		FR-A- 1601089	10-08-70
		GB-A- 1264981	23-02-72
		NL-A- 6902155	17-09-69
US-A-3637503	25-01-72	NONE	
EP-A-88453	14-09-83	AU-B- 572449	12-05-88
		AU-A- 1234283	15-09-83
		CA-A- 1208196	22-07-86
		JP-B- 2038632	31-08-90
		JP-A- 59089397	23-05-84
		US-A- 4956122	11-09-90
EP-A-361180	04-04-90	JP-A- 2092995	03-04-90
		CA-A- 1329803	24-05-94
		PT-B- 91859	29-12-95
		US-A- 5049291	17-09-91

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC/US 96/17414

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-2524118	04-12-75	JP-A- 50151903	06-12-75
		JP-B- 57040197	25-08-82
		GB-A- 1498438	18-01-78
		US-A- 4031020	21-06-77

GB-A-1124016		BE-A- 640804	04-06-64
		BE-A- 673851	16-06-66
		CH-A- 446583	
		DE-B- 1282824	
		DE-B- 1297797	
		FR-E- 89144	09-08-67
		FR-A- 1376127	08-02-65
		GB-A- 1057368	
		NL-A- 300930	
		SE-B- 301359	04-06-68

GB-A-1057368		BE-A- 640804	04-06-64
		BE-A- 673851	16-06-66
		CH-A- 446583	
		DE-B- 1282824	
		DE-B- 1297797	
		FR-E- 89144	09-08-67
		FR-A- 1376127	08-02-65
		GB-A- 1124016	
		NL-A- 300930	
		SE-B- 301359	04-06-68

EP-A-240813	14-10-87	JP-B- 7037623	26-04-95
		JP-A- 62240385	21-10-87
		CA-A- 1277309	04-12-90
		DE-A- 3786289	29-07-93
		DE-T- 3786289	18-11-93

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.